

# AKEBONO OB-360N – Fact Sheet



Akebono taping machines not only work quickly, but are also reliable and can be used anywhere due to their mobility. The paper tape used is available in white or brown and can be quickly removed by the customer by simply tearing it open. In addition, the transparent film offers an optimal display effect and high tear resistance. With individually printed tape, the range of applications is extended even further.

A special highlight of the OB-360N is the usability of extra thin foil tape. The costs for consumables are halved to exactly 50% compared to the previous 110 my thick foil! Of course, the previous foils and paper tapes in white or brown can still be used.

Another exclusive innovation is the metal tape guide frame, which is largely insensitive to static charging, as well as the newly designed and wear-free heating element. Cam levers equipped with dampers ensure smooth machine operation, and the photocell-monitored banding material prevents empty loops that used to occur due to incorrect banding and could cause malfunctions.



1000 Meter Band dispenser



Printed paper bands



Banknote bundle banded

## Akebono OB-360 – Technical data

Brand, make	Akebono
Closure type	Weld closure by means of heat tongue
Band material	Foil, paper
Bandwidths	29 mm
Working height	237 mm (+ Table height)
Frame dimension width x height	489 x 238 mm
Bundle / package width (min / max)	30 bis 420 mm
Bundle / package height (min / max)	10 bis 210 mm
Cycles per min.	26 - 30
Tape tension	0.5 bis 3.0 kg
Band tension adjustment	Mechanical
Roller core-Ø	40 mm
Length	570 mm
Wide	282 mm
Height	489 mm
Electrical connection	230V; 50Hz; 1Ph, 115V; 50/60Hz; 1Ph
Weight	25.40 kg