

# ATLAS-1200 LS – fact sheet

The ATLAS-1200 LS is your reliable partner for processing rectangular labels in the small format range.

All work steps such as buffering, stack cutting, separating and banding run fully automatically and with the utmost precision.

With the "XS Label" option, even the smallest tax marks down to a minimum format of 10 x 28mm can be cut and banded with maximum production reliability. Banding of stacks/maxi-packs is also possible with the ATLAS-1200 LS without any problems.



Strip infeed



Cross-cutting



Separating



Banding

## ATLAS-1200 LS – Technical data

	Standard	XS-Option	XXS-Option
<b>Strip sizes:</b>			
Strip length min. / max.	350 / 1115 mm	350 / 1115 mm	350 / 1115 mm
Strip width min. / max.	45 / 215 mm	30 / 205 mm	28 / 205 mm
<b>Label sizes:</b>			
Precut label size min.	25 x 45 mm	11 x 30 mm	10 x 28 mm
Precut label size max.	170 x 215 mm	170 x 215 mm	170 x 215 mm
Stack height min. / max.	40 / 120 mm	35 / 100 mm	35 / 100 mm
Intermediate trim cut	3 – 40 mm	3 – 40 mm	3 – 40 mm
Trim cut	3 – 40 mm	3 – 40 mm	3 – 40 mm
Rest cut	25 – 100 mm	25 – 100 mm	25 – 100 mm
Bandwidth	25 mm standard 15 mm optional	25 mm standard 15 mm included	25 mm standard 15 mm included
<b>Further details:</b>			
Machine strokes/ minute	15 – 20		
Machine control	PLC (B&R)		
Electrical connection	400V 3.N.PE 6.7 kVA		
Air consumption incl. 30% reserve	6 bar dry air 22 m³/h		
Air connection	½"		
Weight net / gross	2200 / 2600 kg		